


Product overview

Plastic Modular Belt Series



Straight Running Belt Overview

<p>Pitch 8.00 mm (0.32 in)</p> <p>Running direction</p>	<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>	<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>	<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>
<p>uni NTB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>2000 N/m (137 lbf/ft)</p>	<p>uni M-PNB M1 Strength Index (POM)</p> <p>20000 40000 60000</p> <p>2000 N/m (137 lbf/ft)</p>	<p>uni M-QNB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>19000 N/m (1302 lbf/ft)</p>	<p>uni M-SNB M3 Strength Index (POM)</p> <p>20000 40000 60000</p> <p>15000 N/m (1028 lbf/ft)</p>
<p>Pitch 12.7 mm (0.50 in)</p> <p>Running direction</p>	<p>Pitch 19.1 mm (0.75 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>
<p>uni M-TTB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>22500 N/m (1541 lbf/ft)</p>	<p>uni Light Strength Index (POM)</p> <p>20000 40000 60000</p> <p>10250 N/m (702 lbf/ft)</p>	<p>uni CNB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>15700 N/m (1076 lbf/ft)</p>	<p>uni JCB Y Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>
<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>	<p>Pitch 25.4 mm (1.00 in)</p> <p>Running direction</p>
<p>uni LPB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>	<p>uni QNB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>35000 N/m (2400 lbf/ft)</p>	<p>uni S-MPB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>23500 N/m (1610 lbf/ft)</p>	<p>uni SNB M2 Strength Index (POM)</p> <p>20000 40000 60000</p> <p>23500 N/m (1610 lbf/ft)</p>
<p>Pitch 27.9 mm (1.10 in)</p> <p>Running direction</p>	<p>Pitch 38.1 mm (1.50 in)</p> <p>Running direction</p>	<p>Pitch 38.1 mm (1.50 in)</p> <p>Running direction</p>	<p>Pitch 50.0 mm (1.97 in)</p> <p>Running direction</p>
<p>uni OWL Strength Index (POM)</p> <p>20000 40000 60000</p> <p>12000 N/m (822 lbf/ft)</p>	<p>uni Light EP Strength Index (POM)</p> <p>20000 40000 60000</p> <p>10250 N/m (703 lbf/ft)</p>	<p>uni SSB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>36000 N/m (2467 lbf/ft)</p>	<p>uni L-SNB Strength Index (POM)</p> <p>20000 40000 60000</p> <p>55000 N/m (3770 lbf/ft)</p>



Straight Running Belt Overview




uni OPB
Strength Index (POM)





uni BLB
Strength Index (POM)




uni CPB
Strength Index (POM)




uni CSB
Strength Index (POM)





uni ECB
Strength Index (POM)




uni MPB
Strength Index (POM)




uni RTB M1
Strength Index (POM)




uni ULB
Strength Index (POM)



uni X-MPB
Strength Index (POM)




uni XLB
Strength Index (POM)





For further information,
please find the latest
version of our modular
datasheets at:
www.unichains.com



Side Flexing Belt Overview





uni Flex ASB
Strength Index (POM)





uni Flex OSB
Strength Index (POM)





uni Flex SNB
Strength Index (POM)





uni Flex ONE
Strength Index (POM)



uni Flex L-ASB
Strength Index (POM)



uni Flex L-OSB
Strength Index (POM)



Expert advice, quality solutions and local service for all your belting needs
www.ammeraalbeltech.com

Global Headquarters:
Ammeraal Beltech Holding B.V.
P.O. Box 38, 1700 AA Heerhugowaard
The Netherlands

T +31 72 575 1212
F +31 72 571 6455
info@ammeraalbeltech.com